

MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

SUPPLIER NAM	E : M/s. MAXWORTH MINRALS TRADING PVT. LTD.,
ADDRESS	: D No. 48-14-116/6,
	4 [™] FLOOR, LAKSHMI ROYAL PLAZA,
	RESAPUVANIPALEM,
	VISKAHAPATNAM: 530003, AP, INDIA
Tel	: (91) 891 256 6263,
E-MAIL	: <u>enquiry@maxworthgroup.com.au</u>
Web	: <u>www.maxworthgroup.com.au</u>

RISK PHRASES:

R20	: HARMFUL BY INHALATION.
R36/37/38	: IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN
R40	: LIMITED EVIDENCE OF CARCINOGENIC EFFECT
/	

R48/20 : HARMFUL DANGER OF SERIOUS DAMAGE TO HEALTH BY PROLONGED THROUGH INHALATION.

2. HAZARDOUS IDENTIFICATION: CLASSIFIED AS NON-HAZARDOUS ACCORDING TO ASCC CRITERIA

RISK PHRASES:

R20 : HARMFUL BY	INHALATION.
------------------	-------------

- R36/37/38 : IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN
- R40 : LIMITED EVIDENCE OF CARCINOGENIC EFFECT
- R48/20 : HARMFUL DANGER OF SERIOUS DAMAGE TO HEALTH BY PROLONGED THROUGH INHALATION.

SAFETY PHRASES:

S22	: DO NOT BREATH DUST
S24/25	: AVOID CONTACT WITH SKIN AND EYES
S36/37/39	: WEAR SUIATBLE PROTECTIVE CLOTHING, GLOVES AND EYE/FACE PROTECTION.
S38	: IN CASE OF INSUFFICIENT VENTILLATION, EAR SUIATBLE RESPIRATORY EQUIPMENT
S51	: USE ONLY IN WELL VENTILATED AREAS
NOT CLASSIF	ED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE
UN NO.	: NONE ALLOCATED
PACKING GRO	DUP: NONE ALLOCATED
DG CLASS	: NONE ALLOCATED
HAZCHEM CO	DDE: NONE ALLOCATED
SUBSIDIARY F	RISKS(S): NONE ALLOCATED
EPG	: NONE ALLOCATED

Maxworth International Pty Ltd



3. COMPOSITION / INFORMATION ON INGREDIENTS:

Ingredient	Formula	CAS No.	Content
QUARTZ (SILICA CRYSTALLINE)	Si-02	14808-60-7	60-70%
CALCIUM OXIDE	Ca-O	1305-78-8	<12%
IRON OXIDE	Fe2-O3	1309-37-1	<4%
ALUMINIUM OXIDE	AL2-03	1344-28-1	10-20%
MAGNESIUM OXIDE	MG-0	1309-48-4	<1%

4. FIRST AID MEASURES:

Eye	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a poisons information centre, a doctor, or for at least 15 minutes
Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a poisons information centre or a doctor.
Ingestion	For advice, contact a poisons information centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting
Advice to Doctor	Treat symptomatically

5. FIREFIGHTING MEASURES

Flammability	Non-Flammable. May evolve toxic gases if strongly heated.
Fire and explosion	No fire or explosion hazard exists.
Extinguishing	Prevent contamination of drains or waterways.
Hazchem code	None allocated

6. ACCIDENTAL RELEASE MEASURES:

Spillage	Contact emergency services if required. Use personal protective
	equipment. Clear areas of all unprotected personnel. Ventilate area
	where possible. Contain spillage, then cover / absorb spill with non-
	combustible absorbent material (vermiculite, sand, or similar), collect
	and place in suitable containers for disposal. Avoid generating dust.

Maxworth International Pty Ltd



7. STORAGE AND HANDLING:

Storage	Store tightly sealed in a cool, dry, well ventilated area, removed from acids, alkalis, heat or ignition sources and food stuffs. Ensure containers are adequately labeled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills.
Handling	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION:

Exposure Stds	Ingredient	Reference	TWA		STEL	
			ppm	<u>Mg</u> M3	ppm	<u>Mg</u> M3
	Silica, Crystalline Quartz	ASCC (AUS)	-	0.1	-	-]
Biological limits	No biological limit a	llocated			Į.	$\sim \downarrow_{r}$
Engineering Controls	Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.					
PPE	Wear dust-proof goggles and rubber or PVC gloves. When using large quantities or where heavy contamination is likely, wear: coveralls. At high dust levels, wear: a Full-face class P3 (Particulate) or an Air-line respirator. Where an inhalation risk exists, wear: a class P1 (Particulate) respirator.					

9. PHYSICAL & CHEMICAL PROPERTIES

Appearance	GRAY POWDER	Solubility (water)	< 50 g/L
Odour	ODOURLESS	Specific Gravity	2.15 to 2.25
Ph	3 to 4	% Volatiles	< 2%
Vapour Pressure	Not available	Flammability	Non Flammable
Vapour Density	Not available	Flash point	Not relevant
Boiling Point	Not available	Upper explosion limit	Not r <mark>elevant</mark>
Melting Point	>1600 °C	Lower explosion limit	Not rel <mark>evant</mark>
Evaporation Rate	Not available		
Bulk density	800-1000 Kg/m3		

Maxworth International Pty Ltd



10. STABILITY & REACTIVITY

Chemical stability	Stable under recommended conditions of storage
Conditions to avoid	Avoid contact with incompatible substances.
Material to avoid	Incompatible with acids (e.g. nitric acid) and alkalis (e.g. hydroxides)
Decomposition	May evolve toxic gases if heated to decomposition.
Hazardous reactions	Polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Health hazard summary	Irritant. Use safe work practices to avoid eye or skin contact and inhalation. Chronic exposure to crystalline silica may result in lung fibrosis (silicosis). However, due to the low levels of crystalline silica, chronic health effects are not anticipated with normal use. Crystalline silica is classified as carcinogenic to humans (IARC Group 1)	
Eye	Irritant. Contact may result in irritation, lacrimation, pain, redness and conjunctivitis. May result in burns with prolonged contact.	
Inhalation	High Chronic toxicity – irritant. Over exposure to dust may result in mucous membrane irritation of the respiratory tract. Chronic exposure to crystalline silica may result in silicosis (lung fibrosis). Crystalline silica is classified as carcinogenic to humans (IARC Group 1).	
Skin	Irritant. Contact may result in irritation, redness, pain and rash. May cause sensitization by skin contact	
Ingestion	Low to moderate toxicity. Ingestion may result in gastrointestinal irritation, nausea, vomiting, abdominal pain and diarrhoea.	
Toxicity data	Quartz (Silica Crystalline) (14808-60-7)LCLo (Inhalation) : 300 ug/m3/10 years (human)LDLo (Intravenous) : 200 mg/kg (rat)LDLo (Intravenous) : 20 mg/kg (dog)TCLo (Inhalation) : 16 000 000 particles / ft3/8 hours/17.9 years(human-fibrosis)	

12. ECOLOGICAL INFORMATION

Environment	The main component/s of this product are not anticipated to cause any
	adverse effects to plants or animals.

13. DISPOSAL CONSIDERATION

Waste disposal	Ensure product is covered with moist soil to prevent dust generation and dispose to approved council landfill. Contact the manufacturer if
	additional information is required.
Legislation	Dispose of in accordance with relevant local legislation

Maxworth International Pty Ltd



14. TRANSPORT INFORAMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE		
Shipping Name: None allocated		
UN No. None allocated	DG Class : None allocated	Subsidiary Risk(s): None
		allocated
Packing group: None allocated	Hazchem group: None	EPG: None allocated
	allocated	

15. REGULATORY INFORMATIONS

Poison Schedule	A poison schedule number has not been allocated to this product using the criteria in the standard for the uniform scheduling of drugs and poisons (SUSDP)
AICS	All chemicals listed on the Australian Inventory of Chemical substances (AICS)

16. OTHER INFORMATION

r	
Additional Information	Crystalline silica is present in Fly Ash as an impurity. The amount
	depends on the crystalline silica content of the source coal.
	ALUMINO SILICATES: When alumina silicates have been exposed to
	service temperatures exceeding 982° C for prolonged periods,
	cristobalite, a form of crystalline silica may be formed. Exposure to
	cristobalite dust may cause pulmonary fibrosis-silicosis. A hazard is only
	anticipated during demolition of used refractory materials. Cristobalite
	is classified as carcinogenic to humans (IARC Group 1)
	RESPIRATORS: In general, the use of respirators should be limited and
	engineering controls employed to avoid exposure. If respiratory
	equipment must be worn ensure correct respirator selection and training
	is undertaken. Remember that some respirators may be extremely
	uncomfortable when used for long periods. The use of air supplied
	respirators should be considered where prolonged or repeated use is
	necessary.
	ABBREVIATIONS:
	ADB - Air Dry basis
	BEI-Biological exposure indices(s)
	CAS# - Chemical abstract service number-used to uniquely indentify
	chemical compounds
	CNS - Central Nervous System
	EINECS - European inventory of existing commercial chemical substances
	IARCS - International agency for research on cancer
	M - moles per ltr, a unit of concentration.
	Mg/m3 - Milligrams per cubic mtr
	NOS - Not otherwise specified
	NTP - National toxicology program
	OSHA - Occupational safety fir health administration
	pH - relates to hydrogen ion concentration using a scale of 0(high acidic)

Maxworth International Pty Ltd



	to 14 (highly alkaling)
	to 14 (highly alkaline) ppm - Parts per million
	RTECS - registry of toxic effects of chemical substances
	TWA/ES -Time weighted average or exposure standard.
	HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects
	from exposure to this product will depend on several factors including:
	frequency and duration of use; quantity used; effectiveness of control
	measures; protective equipment used and method of application. Given
	that it is impractical to prepare a CChem Alert report which would
	encompass all possible scenarios, it is anticipated that users will assess
	the risks and apply control methods where appropriate.
	PERSONAL PROTECTIVE EQUIPMENT GUIDELINES : The recommendation
	for protective equipment contained within this Chem Alert is provided as
	a guide only. Factors such as methods of application, working
	environment, quantity used, product concentration and the availability
	of engineering controls should be considered before final selection of
	personal protective equipment is made.
Report Status:	This docum <mark>ent has been com</mark> piled by RMT on behalf of the manufacturer
	of the product and serves as the manufacturers safety data sheet ('SDS').
	It is based on information concerning the product which has been
	provided to RMT by the manufacturer or obtained from third party
	sources and is believed to represent the current state of knowledge as to
	the appropriate safety and handling precautions for the product at the
	time of issue. Further clarification regarding any aspect of the product
	should be obtained directly from the manufacturer.
	While RMT has taken all due care to include accurate and up-to-date
	information in this SDS, it does not provide any warranty as to accuracy
	or completeness. As far as lawfully possible, RMT accepts no liability for
	any loss, injury, or damage (including consequential loss) which may be
	suffered or incurred by any person as a consequence of their reliance on
	the information contained in this SDS.
Prepared by	M/S. MAXWORTH MINERALS TRADING PVT. LTD.,
	D No 48-14-116/6, LAKSHIMI ROYAL PLAZA,
	FOURTH FLOOR, RESAPUVANIPALEM,
	VISAKHAPATNAM – 530003, INDIA
	TEL: (91) 891 256 6263

Maxworth International Pty Ltd